

# DUO-SIL<sup>®</sup>

## HIGH PERFORMANCE, ONE COMPONENT, URETHANE ACRYLIC SEALANT AND ADHESIVE.

**DUO-SIL<sup>®</sup>** is a caulking compound that can be used to fill joints in vinyl, aluminum and cement sidings, windows, doors, brick molding, counter tops, showers and most areas where a sealant is needed. **DUO-SIL<sup>®</sup>** as an adhesive has superior bond to most building substrates and will adhere to wood, metal, gypsum board, vinyl, PVC, cove base, molding, foam board and many more building products.

- Superior adhesion and sealing
- Available in more than 140 stock colors and clear
- Unmatched ease of application and easy water cleanup
- Paintable in less than two hours
- Excellent UV and mildew resistant
- Interior/exterior applications including siding, windows, doors, trim and moldings
- Environmentally safe, non-hazardous, non-flammable, and low VOC
- Meets or exceeds standard specification for latex sealants ASTM C-834-00, type C, grade 0°C
- Two-piece plastic cartridge will not deteriorate when exposed to the elements
- 4" detachable nozzle for repeated use and increased efficiency



**Siroflex<sup>®</sup>**  
incorporated

Siroflex Inc. PO Box 26749 Greenville, SC 29616 • 800.359.6398  
cservice@siroflexinc.com • www.siroflexinc.com

**Siroflex<sup>®</sup>**

SEALANTS



**DUO-SIL<sup>®</sup>**  
**URETHANE ACRYLIC**  
**SEALANT AND ADHESIVE**

**Interior/exterior grade.** High performance acrylic and urethane emulsion sealant that can be used as a caulking compound and an adhesive. **DUO-SIL<sup>®</sup>** will not degrade Polystyrene foam bead board. (Available in white, clear and 140 colors. Clear applies white and cures clear.)

SPECIFICATIONS: Meets or exceeds the Standard Specification for Latex Sealants ASTM C-834-00, Type C, Grade 0° C.

Net Contents: 10.1 oz. (299 ml)  
Made in USA • Printed in USA

## Other Siroflex products include:

### ACRY-SIL

PREMIUM QUALITY. SILICONIZED ACRYLIC SEALANT FOR BOTH INTERIOR AND EXTERIOR APPLICATIONS

**ACRY-SIL**® is a high performance siliconized acrylic latex sealant with excellent adhesion and weatherability. ACRY-SIL displays outstanding handling characteristics and is easy to clean-up with water. ACRY-SIL is paintable with latex or oil based paints.



### DUO-SIL

HIGH PERFORMANCE, ONE COMPONENT, URETHANE ACRYLIC SEALANT AND ADHESIVE. NON-HAZARDOUS, NON-FLAMMABLE, MILDEW RESISTANT

**DUO-SIL**® is a special formulation of urethane and acrylic emulsion formulated for the professional applicator which can be used as an adhesive or caulking compound for commercial and residential construction.



### DUO-SIL ULTRA

HIGH PERFORMANCE, ALL-WEATHER SEALANT, NON-HAZARDOUS, NON-FLAMMABLE, MILDEW RESISTANT

**DUO-SIL ULTRA**® is specifically designed to meet the needs of the professional contractor. It is a superior, all-purpose adhesive and sealant combining enhanced ease of application with long-term performance.



### HYBRI-SIL

ALL WEATHER SEALANT, ADVANCED HYBRID POLYMER ADHESIVE/SEALANT


**HYBRI-SIL**® is an adhesive/sealant based on MS Polymer chemistry. The product is odorless, neutral and isocyanate free. The low VOC formula meets American and European safety and environmental regulations regarding the emission of volatile organic compounds (VOCs).



### SIR-O-SIL 25

HIGH PERFORMANCE, HIGH MODULUS, ONE COMPONENT, ACETOXY CURE SILICONE SEALANT


**SIR-O-SIL 25**® is an easy to apply, one component sealant that cures to a durable, flexible, silicone rubber upon exposure to atmospheric moisture while giving off a small amount of acetic acid. SIR-O-SIL 25 has been specifically designed for fast curing and excellent adhesion to non-porous surfaces such as glass, metals and ceramics. SIR-O-SIL 25 is a highly flexible silicone sealant that accommodates joint movement of +/- 25%.



### SIR-O-SIL 50

HIGH PERFORMANCE, LOW MODULUS, ONE-COMPONENT, GENERAL PURPOSE SEALANT FOR PROFESSIONAL CAULKING, GLAZING, AND INDUSTRIAL APPLICATIONS

**SIR-O-SIL 50**® is a versatile, neutral cure, one component high performance low modulus silicone. SIR-O-SIL 50 reacts with atmospheric moisture to produce a flexible silicone rubber. SIR-O-SIL 50 is ideal for a wide variety of general purpose caulking, glazing, and industrial applications. SIR-O-SIL 50 provides high movement capability as well as excellent weatherability.



## WINDOW & DOOR FOAM SEALANT

**SIROFLEX® WINDOW & DOOR FOAM SEALANT** is a single component minimal expanding polyurethane sealant. Siroflex® foam sealant creates a water resistant bond to vinyl, wood and metal frames, making it ideal for filling cracks and voids where air can penetrate.



## GUTTER & SEAM SEALER

**SIROFLEX® GUTTER & SEAM SEALER** is a single component sealant that forms a water tight durable, flexible seal in gutters and narrow seams. All-weather application, including through standing water. Can be applied from -40°F to 140°F.

