

GUTTER & SEAM SEALER

GUTTER AND NARROW SEAM SEALANT. SEMI-SELF LEVELING, SINGLE COMPONENT, PAINTABLE

product description

SIROFLEX GUTTER & SEAM SEALER is a single component sealant that forms a watertight, durable, flexible seal in gutters and narrow seams. All weather application, including through standing water. Can be applied from -40°F to 140°F.

basic uses

SIROFLEX GUTTER & SEAM SEALER has been developed for building construction and industrial applications. This narrow seam sealant is particularly effective for sealing gutter lap joints, end caps and slip joints. Other applications include:

- Sealing downspout joints
- Sealing storm windows
- Sealing flashing
- Sealing joints in metal awnings
- Sealing joints in vents
- Sealing thresholds

features

- Semi-self leveling single component sealant
- Excellent gunnability throughout a wide temperature range
- Service temperature range of -40°F to 180°F
- Can be applied in any weather condition, through standing water, even on oily surfaces
- Paintable
- Excellent adhesion to most building surfaces, including asphalt
- Excellent ultraviolet resistance

packaging

SIROFLEX GUTTER & SEAM SEALER is available in 10.6 fl oz (314ml) cartridges, packed 12 cartridges per case, and 5 fl.oz (148ml) squeeze tubes, packed 24 per case.

limitations

- Do not apply to Polystyrene Foam
- Not recommended for use in joints larger than 1/4" x 1/4"
- Not for use on traffic bearing surfaces
- Read directions and caution statements printed on cartridge or squeeze tube prior to use
- Allow 24 hrs. prior to painting with latex and most oil based paints

typical properties

These values are not intended for use in preparing specification.

Application Temperature: -40°F to 140°F

Tack Free Time: 20 hours

Cure Time (1/4" x 1/4" bead) 5 days

Temperature Resistance: -40°F to 180°F

Paintability: After 24 hours with latex and most oil based paints

Cleaning: Uncured sealant with solvents such as lacquer thinner, Xylol or Tuluol

Shelf Life: 12 months unopened cartridge or tube

Storage: Cool, dry conditions

precautions

- COMBUSTIBLE during cure
- Apply with adequate ventilation
- Do not swallow, avoid contact with eyes
- Do not induce vomiting if swallowed. Contact a physician immediately
- Keep out of reach of children.

availability

Immediately available from Siroflex distributors strategically located throughout the U.S.

cost

Cost information is available from your local Siroflex Distributor or by calling our customer service department at 1-800-359-6398.

NOTICE TO PURCHASER: Siroflex warrants its products to conform to Siroflex published specifications. The user shall determine the suitability of the product to their particular application. THE FOREGOING WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THOSE OF THE MERCHANTABILITY OR FITNESS FOR ANY PURPOSE NOT EXPRESSLY SET FORTH HEREIN. Manufacturer's and seller's liability for damage hereunder shall not exceed the purchase value of the goods used. IN NO EVENT SHALL MANUFACTURER OR SELLER BE RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF THIS PRODUCT BY BUYER, BUYER'S USER, OR ANY OTHER PERSON. Notification of claim must be sent in writing to Siroflex, Inc. The notice should contain a statement as to how the product failed to meet our warranty, the proof of purchase and the amount of refund claimed.

CAUTIONS: CONTAINS AROMATIC HYDROCARBONS. KEEP AWAY FROM SPARKS AND OPEN FLAME.

MSDS ALSO AVAILABLE AT WWW.SIROFLEXINC.COM

For Commercial Applications Contact Siroflex at 1.800.359.6398

PO BOX 26749 • GREENVILLE, SC 29616 • 800.359.6398 • 864.458.9094 • FAX 864.458.9092

GSS001 / 2013

WWW.SIROFLEXINC.COM • ORDERS@SIROFLEXINC.COM

Siroflex®

GSS-001 | 2013