

DUO-SIL ULTRA[®]

ADVANCED HYBRID POLYMER TECHNOLOGY ADHESIVE/SEALANT

DUO-SIL ULTRA[®] is specifically designed to meet the needs of the professional contractor. It is a superior, all-purpose adhesive and sealant combining enhanced ease of application with long-term performance. Duo-Sil Ultra[®] can be applied from 0° to 140°F, on wet, damp, or dry surfaces and is ready to paint one hour after application. Duo-Sil Ultra[®] is formulated to withstand the harshest weather conditions, from extreme cold to driving rain to hot and humid conditions. It will never shrink, crack, or peel and has a low VOC formulation containing no isocyanates or solvents.



All Weather Application



Paintable Surface



Wet Surface Application



Interior and Exterior

- All weather application - wet, damp, dry surfaces
- 0°-140° F application temperature
- Paintable in one hour
- Available in 140+ colors
- Meets or exceeds the requirements of ASTM C920, Class 50
- Meets the performance requirements of AAMA 803.3-10
- Interior/exterior applications including siding, windows, doors, trim and moldings
- Superior adhesion and sealing
- Environmentally safe, non-hazardous, non-flammable, and low VOC
- Non-yellowing formula
- Two-piece plastic cartridge will not deteriorate when exposed to the elements
- 4" detachable nozzle for repeated use and increased efficiency
- Ideal for use with fiber cement siding, vinyl siding, windows, aluminum, wood, mortar, brick, and more



Other Siroflex products include:

ACRY-SIL

PREMIUM QUALITY. SILICONIZED ACRYLIC SEALANT FOR BOTH INTERIOR AND EXTERIOR APPLICATIONS

ACRY-SIL® is a high performance siliconized acrylic latex sealant with excellent adhesion and weatherability. ACRY-SIL displays outstanding handling characteristics and is easy to clean-up with water. ACRY-SIL is paintable with latex or oil based paints.



DUO-SIL

HIGH PERFORMANCE, ONE COMPONENT, URETHANE ACRYLIC SEALANT AND ADHESIVE. NON-HAZARDOUS, NON-FLAMMABLE, MILDEW RESISTANT

DUO-SIL® is a special formulation of urethane and acrylic emulsion formulated for the professional applicator which can be used as an adhesive or caulking compound for commercial and residential construction.



DUO-SIL ULTRA

HIGH PERFORMANCE, ALL-WEATHER SEALANT, NON-HAZARDOUS, NON-FLAMMABLE, MILDEW RESISTANT

DUO-SIL ULTRA® is specifically designed to meet the needs of the professional contractor. It is a superior, all-purpose adhesive and sealant combining enhanced ease of application with long-term performance.



HYBRI-SIL

ALL WEATHER SEALANT, ADVANCED HYBRID POLYMER ADHESIVE/SEALANT


HYBRI-SIL® is an adhesive/sealant based on MS Polymer chemistry. The product is odorless, neutral and isocyanate free. The low VOC formula meets American and European safety and environmental regulations regarding the emission of volatile organic compounds (VOCs).



SIR-O-SIL 25

HIGH PERFORMANCE, HIGH MODULUS, ONE COMPONENT, ACETOXY CURE SILICONE SEALANT


SIR-O-SIL 25® is an easy to apply, one component sealant that cures to a durable, flexible, silicone rubber upon exposure to atmospheric moisture while giving off a small amount of acetic acid. SIR-O-SIL 25 has been specifically designed for fast curing and excellent adhesion to non-porous surfaces such as glass, metals and ceramics. SIR-O-SIL 25 is a highly flexible silicone sealant that accommodates joint movement of +/- 25%.



SIR-O-SIL 50

HIGH PERFORMANCE, LOW MODULUS, ONE-COMPONENT, GENERAL PURPOSE SEALANT FOR PROFESSIONAL CAULKING, GLAZING, AND INDUSTRIAL APPLICATIONS

SIR-O-SIL 50® is a versatile, neutral cure, one component high performance low modulus silicone. SIR-O-SIL 50 reacts with atmospheric moisture to produce a flexible silicone rubber. SIR-O-SIL 50 is ideal for a wide variety of general purpose caulking, glazing, and industrial applications. SIR-O-SIL 50 provides high movement capability as well as excellent weatherability.



WINDOW & DOOR FOAM SEALANT

SIROFLEX® WINDOW & DOOR FOAM SEALANT is a single component minimal expanding polyurethane sealant. Siroflex® foam sealant creates a water resistant bond to vinyl, wood and metal frames, making it ideal for filling cracks and voids where air can penetrate.



GUTTER & SEAM SEALER

SIROFLEX® GUTTER & SEAM SEALER is a single component sealant that forms a water tight durable, flexible seal in gutters and narrow seams. All-weather application, including through standing water. Can be applied from -40°F to 140°F.

